




# **COMPARISON OF LUMINOUS DISTRIBUTION OF MALAYSIAN SKY WITH THE NAKAMURA MODEL**

**MOHD YASIN BIN HAJI ALWI  
(2002334748)**

**BACHELOR ENGINEERING (HONS) MECHANICAL  
UNIVERSITI TEKNOLOGI MARA (UiTM)  
DECEMBER 2005**

"I declare that this thesis is the result of my own work except the ideas and summaries which I have clarified their sources. The thesis has not been accepted for any degree and is not concurrently submitted in candidature of any degree."

Signed :   
Date : 8 DECEMBER 2005

**Mohd Yasin Bin Haji Alwi**  
UiTM No: 2002334748

## ABSTRACT

In Malaysia, solar energy studies are considered new. The applications of solar energy in Malaysia can be classified into two categories which are thermal systems and photovoltaic systems. Thermal systems mean the conversion of solar energy into thermal energy and photovoltaic systems mean the conversion of solar energy into electrical energy. The availability and cost of energy have become dominant factors in society today. Therefore, renewable energy resources are expected to cover the energy scenarios of the future energy consumptions. Solar energy is practically unlimited, environmentally clean, and friendly. Solar energy is expected to play a very significant role in the future especially in developing countries, but it has also potential prospects for developed countries. But, solar energy is intermittent because night and day, cloudy days, and seasons of the year. Consequently, it must be collected when available and stored in large quantities and used later as energy. Basically in this study, the development of experimental data that provides the daylight data in Malaysian Sky, specifically in Shah Alam is the target that needs to be achieved.

The purpose of this project is to compare the Luminous Distribution (LD) of Malaysian Sky with the Japanese Sky, given as the Nakamura Model. The value of Luminance of Malaysian Sky is also measured and analysed. From this study, it can be concluded that Luminous Distribution of Malaysian Sky does not exactly follow the Nakamura Model. The LD of Malaysian Sky only valid to Nakamura Model at certain period of time which falls between 11.30 am until 2.30 pm. The highest value of Luminance by average was recorded at 1.30 pm with the value of  $12.98 \text{ kcd/m}^2$ .

**TABLE OF CONTENTS**

<b>CONTENTS</b>	<b>PAGE</b>
PAGE TITLE	I
ACKNOWLEDGEMENT	II
ABSTRACT	III
TABLE OF CONTENTS	IV
LIST OF TABLES	VII
LIST OF FIGURES	VIII

**CHAPTER I            INTRODUCTION**

1.0	Background of the study	1
1.1	Solar Energy	
1.1.1	Solar Energy as a Part of the Renewable Energy	2
1.1.2	Solar Energy Technology Applications in Malaysia	3
1.2	Sky Luminance and illuminance	4
1.2.1	Fundamentals of daylighting that related to Luminance and Illuminance	5

1.3	Sky Models: Nakamura Model	6
1.4	Objectives of project	8

## **CHAPTER II      METHODOLOGY**

2.0	Sky Scanner	9
2.0.1	General Description & Characteristic	9
2.0.2	Installation of Sky Scanner at Monitoring station	10
2.1	Methodology	
2.1.1	Experimental Arrangement	11
2.1.1.1	Preparation before setting up the Sky Scanner	11
2.1.1.2	Preparation for setting up the Sky Scanner	14
2.1.1.2.1	Installation of the Sky Scanner	14
2.1.1.2.2	Connection of Sky Scanner	17
2.1.1.3	The way the experiment was conducted	18
2.1.1.4	Instrumentation	20
2.1.1.5	Analysis Method	21

## **CHAPTER III      RESULTS AND DISCUSSIONS**

3.0	Luminance Value	25
3.1	Luminous Distribution	32
3.2	Luminous Distribution of Malaysian Sky compared to Nakamura Model	32